

Tysnes 66



Tysnes 66 1200 Grey 5510lm 4000K Ra>80 DALI-2

Article code: 120039
EAN: 7021981200398



Electrical

Wattage: 34W
System wattage: 34W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 14, B16: 24, C10: 25, C16: 40
Leakage current (mA): 0.29

Light technic

Type of light source: LED
Light source included: Yes
Luminous flux: 5510lm
Efficacy: 157
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Light distribution: Direct
Optic: Opal
Beam angle: 116°

Control/Dimming

Type: DALI-2

Protection

Luminaire class: Class I
IK Class: IK10
IP Class: IP66
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting
Food Safety approved (IFS and HACCP): Yes

Materials and finish

Housing: UV-stabilized polycarbonate
Colour: Grey
Optics: UV-stabilized polycarbonate

Mounting/Connection



Mounting: Surface, Indoor
Module: 1200
Connection: 5-pole screwless terminal block with 5x2,5mm² through wiring

Dimensions

Length (mm) L: 1200
Width (mm) W: 85
Height (mm) H: 80
Weight (kg) gross/net: 1.68 / 1.53

Packaging

Packing dimensions (mm): 1225 x 85 x 90



7 0 2 1 9 8 1 2 0 0 3 9 8