

Sense Basic



Sense Basic 625x625 White Incl driver 3930lm 3000K Ra>80 On/Off

Article code: 212141
EAN: 7021982121418



Electrical

System wattage: 35W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 15, B16: 25, C10: 24, C16: 40

Light technic

Type of light source: LED
Luminous flux: 3930lm
Efficacy: 112 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Light distribution: Direct
Optic: Opalprism
UGR: UGR<19
Visible flicker (PstLM): 0.02
Stroboscopic flicker (SVM): 0.02

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class II SELV
IK Class: IK06
IP Class: IP20

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Steel
Colour: White smooth (Ral 9016 gloss 30)
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Recessed, Indoor
Module: 625x625
Connection: Screwless terminal block

Dimensions

Length (mm) L: 620
Width (mm) W: 620
Height (mm) H: 36
Weight (kg) gross/net: 2.6 / 2.4

Packaging

Packing dimensions (mm): 620 x 620 x 36
Number per pack: 4



cd/klm
— C0/C180
— C90/C270

$\eta = 100\%$



7 0 2 1 9 8 2 1 2 1 4 1 8