

Duo White 640lm 3000K Ra>80 Trailing edge

Article code: 212250
EAN: 7021982122507



Electrical

System wattage: 10W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light technic

Type of light source: LED
Luminous flux: 640lm
Efficacy: 64 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B10>50,000
Light distribution: Direct
Optic: Plastic clear
Beam angle: 40° down / 110° up
Photobiological safety: RG 0

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IP Class: IP20

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Aluminium and stainless steel
Colour: Matte white (RAL 9003)
Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Surface, Indoor
Connection: Screwless terminal block

Dimensions

Length (mm) L: 180
Width (mm) W: 170
Height (mm) H: 135
Depth (D): 103
Weight (kg) gross/net: 0.589 / 0.495

Packaging

Packing dimensions (mm): 180 x 110 x 145

