

Sense Round



Sense White 190 IsoSafe 750lm 3000K Ra>80 DALI-2 / Push Dim

Article code: 212266
EAN: 7021982122668



Electrical

System wattage: 7W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 80, B16: 130, C10: 80, C16: 130

Light technic

Type of light source: LED
Luminous flux: 750lm
Efficacy: 107 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Light distribution: Direct
Optic: Opal
UGR: UGR<25
Photobiological safety: RG 0

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class II SELV
IK Class: IK08
IP Class: IP40/IP20

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfil Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White smooth (Ral 9016 gloss 30)
Optics: Acrylic (PMMA)

Mounting/Connection


Mounting: Recessed, Indoor
Connection: 5 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 25
Diameter (mm) D: 190
Cut-out (mm): 170
Ceiling void depth (mm): 25
Weight (kg) gross/net: 0.648 / 0.505

Packaging

Packing dimensions (mm): 195 x 195 x 75



7 0 2 1 9 8 2 1 2 2 6 6 8