

Sense Surface



Sense Surface 300x1600 White 5240lm 4000K Ra>80 Trailing edge

Article code: 212399
EAN: 7021982123993



Electrical

System wattage: 38W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 19, B16: 31, C10: 19, C16: 31

Light technic

Type of light source: LED
Luminous flux: 5240lm
Efficacy: 138 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Light distribution: Direct
Optic: Opalprism
UGR: UGR<19
Visible flicker (PstLM): 0.4
Stroboscopic flicker (SVM): 1

Control/Dimming

Type: Trailing edge
Driver: 1050mA

Protection

Luminaire class: Class II
IK Class: IK10
IP Class: IP20

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Surface, Indoor
Module: 300x1600
Connection: Screwless terminal block

Dimensions

Length (mm) L: 1582
Width (mm) W: 302
Height (mm) H: 45
Weight (kg) gross/net: 8.8 / 7.8

Packaging

Packing dimensions (mm): 1605 x 335 x 65



7 0 2 1 9 8 2 1 2 3 9 9 3