

Inspire R



Inspire R White 150 490lm 4000K Ra 98 Trailing edge

Article code: 212419
EAN: 7021982124198



Electrical

System wattage: 8W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED
Luminous flux: 490lm
Efficacy: 61 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra 98
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Lens
Beam angle: 55°
UGR: UGR<19
Photobiological safety: RG 1

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II SELV
IP Class: IP20

Energy and approvals

Contains light source of energy class: E
Breem: Fulfil Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)

Mounting/Connection


Mounting: Recessed, Indoor
Module: Recessed
Connection: Screwless terminal block

Dimensions

Length (mm) L: 163
Width (mm) W: 62
Height (mm) H: 40
Weight (kg) gross/net: 0.406 / 0.31

Packaging

Packing dimensions (mm): 177 x 121 x 73



7 0 2 1 9 8 2 1 2 4 1 9 8