


# Rax Soft 200



## Rax Soft 200 Satin 2200 4000K Ra>80 DALI-2 / Push Dim

Article code: 212523  
EAN: 7021982125232  
Replaces: 8246092777



### Electrical

System wattage: 18W  
Voltage: 220-240V  
Frequency (Hz): 50/60Hz  
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

### Light technic

Type of light source: LED  
Luminous flux: 2220lm  
Emergency lumen: EM 390lm  
Efficacy: 123 lm/W  
Colour temperature: 4000K  
Colour rendering (Ra): Ra>80  
MacAdams factor: SDCM: 2  
Lifetime: L90/B10>100,000  
Light distribution: Direct  
Optic: Satin Matt Reflector  
Beam angle: 62°  
UGR: UGR<19 up to 600 mA/2640 lm  
Photobiological safety: RG 1

### Control/Dimming

Type: DALI-2 / Push Dim

### Protection

Luminaire class: Class II SELV  
IK Class: IK08  
IP Class: IP54/IP20

### Energy and approvals

Contains light source of energy class: D  
Breeam: Fulfils Hea 01 for flicker free lighting  
BVB: Yes

### Materials and finish

Housing: Flame retardant polycarbonate  
Colour: White/Satin mat  
Optics: Polycarbonat (PC)

### Mounting/Connection


Mounting: Recessed, Indoor  
Cable: Cable 5x0,75mm<sup>2</sup>  
Connection: 5 pol Linect / screwless terminal block

### Dimensions

Height (mm) H: 93  
Diameter (mm) D: 216  
Cut-out (mm): 200  
Ceiling void depth (mm): 90  
Weight (kg) gross/net: 1.2 / 1

### Packaging

Packing dimensions (mm): 240 x 240 x 102



7 0 2 1 9 8 2 1 2 5 2 3 2