

Rax Soft 200 Asymmetric



Rax Soft 200 Satin Asymmetric 1600 3000K Ra>80 DALI-2 / Push Dim

Article code: 212545
EAN: 7021982125454



• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 15W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED
Luminous flux: 1600lm
Emergency lumen: EM 330 lm
Efficacy: 107 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Satin Matt Reflector
Photobiological safety: RG 1

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class II SELV
IK Class: IK08
IP Class: IP54/IP20

Energy and approvals

Breem: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Flame retardant polycarbonate
Colour: White/Satin mat
Optics: Polycarbonat (PC)

Mounting/Connection


Mounting: Recessed, Indoor
Cable: Cable 5x0,75mm²
Connection: 5 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 93
Diameter (mm) D: 216
Cut-out (mm): 200
Ceiling void depth (mm): 90
Weight (kg) gross/net: 1.2 / 1

Packaging

Packing dimensions (mm): 240 x 240 x 102



7 0 2 1 9 8 2 1 2 5 4 5 4