

Rax Soft 200 Black



Rax Soft 200 Black 3000 4000K Ra>80 Trailing edge

Article code: 212566
EAN: 7021982125669



Electrical

System wattage: 30W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 25, B16: 41, C10: 40, C16: 65

Light technic

Type of light source: LED
Luminous flux: 3070lm
Emergency lumen: EM 330 lm
Efficacy: 102 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Black reflector
Beam angle: 63°
UGR: UGR<22
Photobiological safety: RG 1

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II SELV
IK Class: IK08
IP Class: IP54/IP20

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Flame retardant polycarbonate
Colour: Black
Optics: Polycarbonat (PC)

Mounting/Connection

Mounting: Recessed, Indoor
Connection: 3 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 93
Diameter (mm) D: 216
Cut-out (mm): 200
Ceiling void depth (mm): 90
Weight (kg) gross/net: 1.2 / 1

Packaging

Packing dimensions (mm): 240 x 240 x 102

