

Rax Eco 200



Rax ECO 200 White 3000/4000K Ra>80 Trailing edge

Article code: 212569
EAN: 7021982125690



Electrical

Wattage: 13W/24W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 23, B16: 36, C10: 37, C16: 60

Light technic

Type of light source: LED
Luminous flux: 1400lm/1490lm/2310lm/2460lm
Efficacy: 108/115/96/103lm/W
Colour temperature: 3000/4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>50,000
Light distribution: Direct
Optic: Reflector
Beam angle: 95°
UGR: UGR<22
Visible flicker (PstLM): 0.04
Stroboscopic flicker (SVM): 0
Photobiological safety: RG 1

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IP Class: IP20

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Polycarbonat (PC)
Colour: White (RAL 9003)
Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Indoor
Connection: 3 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 93
Diameter (mm) D: 216
Cut-out (mm): 200
Ceiling void depth (mm): 93
Weight (kg) gross/net: 1.03 / 0.87

Packaging

Packing dimensions (mm): 240 x 222 x 120

