

Rax Soft 150



Rax Soft 150 Satin 2200 4000K Ra>90 DALI-2 / Push Dim

Article code: 212571
EAN: 7021982125713



Electrical

System wattage: 22W
Voltage: 220-240V
Frequency (Hz): 50/60Hz

Light technic

Type of light source: LED
Luminous flux: 2310lm
Emergency lumen: EM 320lm
Efficacy: 105 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>90
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Satin Matt Reflector
Beam angle: 68°
UGR: UGR<22 up to 850 mA/3160 lm
Photobiological safety: RG 1

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class II SELV
IK Class: IK08
IP Class: IP54/IP20

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Flame retardant polycarbonate
Colour: White/Satin mat
Optics: Polycarbonat (PC)

Mounting/Connection


Mounting: Recessed, Indoor
Cable: Cable 5x0,75mm²
Connection: 5 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 83
Diameter (mm) D: 166
Cut-out (mm): 150
Ceiling void depth (mm): 80
Weight (kg) gross/net: 0.97 / 0.77

Packaging

Packing dimensions (mm): 160 x 190 x 92



7 0 2 1 9 8 2 1 2 5 7 1 3