

Rax Soft 200 Square



Rax Soft Square 200 Satin 2200 2370lm 3000K Ra>80 Trailing edge

Article code: 212580
EAN: 7021982125805



Electrical

System wattage: 19W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 18, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 2370lm
Efficacy: 125 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Satin Matt Reflector
Beam angle: 62°
UGR: UGR<19 opptil 600 mA
Photobiological safety: RG 1

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II SELV
IK Class: IK08
IP Class: IP54/IP20

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Flame retardant polycarbonate
Colour: White/Satin mat
Optics: Polycarbonat (PC)

Mounting/Connection



Mounting: Recessed, Indoor
Cable: Cable 5x0,75mm²
Connection: 3 pol Linect / screwless terminal block

Dimensions

Length (mm) L: 216
Width (mm) W: 216
Height (mm) H: 93
Ceiling void depth (mm): 90
Weight (kg) gross/net: 1.225 / 1

Packaging

Packing dimensions (mm): 260 x 235 x 100



7 0 2 1 9 8 2 1 2 5 8 0 5