

Rax Soft 200 Square



Rax Soft Square 200 Satin 2370lm 3000K Ra>80 DALI-2 / Push Dim

Article code: 212582
EAN: 7021982125829



Electrical

System wattage: 19W
Voltage: 220-240V
Frequency (Hz): 50/60Hz

Light technic

Type of light source: LED
Luminous flux: 2370lm
Efficacy: 125 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Satin Matt Reflector
Beam angle: 62°
UGR: UGR<19 opptil 600 mA

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class II SELV
IK Class: IK08
IP Class: IP54/IP20

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Flame retardant polycarbonate
Colour: White/Satin mat
Optics: Polycarbonat (PC)

Mounting/Connection



Mounting: Recessed, Indoor
Cable: Cable 5x0,75mm²
Connection: 5 pol Linect / screwless terminal block

Dimensions

Length (mm) L: 216
Width (mm) W: 216
Height (mm) H: 93
Ceiling void depth (mm): 90
Weight (kg) gross/net: 1.225 / 1

Packaging

Packing dimensions (mm): 260 x 235 x 100



7 0 2 1 9 8 2 1 2 5 8 2 9