

Sense 600x600 Round



Sense Pro Round 600x600 White 3860lm 3000K Ra>80 DALI-2 / Push Dim

Article code: 212674+820407
EAN: 7021982126741+7021988204078



Electrical

System wattage: 38W
Max. luminaires per circuit breaker: B10: 35, B16: 55, C10: 55, C16: 91

Light technic

Type of light source: LED
Luminous flux: 3860lm
Efficacy: 102 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Light distribution: Direct
Optic: Opalprism
Beam angle: 110°
UGR: UGR<20
Photobiological safety: RG 0

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class III
IK Class: IK10
IP Class: IP40/IP20

Energy and approvals

Breem: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White smooth (Ral 9016 gloss 30)
Optics: Acrylic (PMMA)

Mounting/Connection



Module: Exposed T-carrier 15/24mm
Connection: Quick connector

Dimensions

Length (mm) L: 597
Width (mm) W: 597
Height (mm) H: 11
Weight (kg) gross/net: 4.055 / 3.55

Packaging

Packing dimensions (mm): 645 x 640 x 43



7021982126741+7021988204078