

Sense Line



Sense Line 120x1200 White Linect 2310lm 3000K Ra>80 DALI-2

Article code: 212695
EAN: 7021982126956



Electrical

System wattage: 19W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 31, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED
Light source included: Yes
Luminous flux: 2310lm
Efficacy: 122 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Light distribution: Direct
Optic: Opalprism
Beam angle: 84°
UGR: UGR<19

Control/Dimming

Type: DALI-2

Protection

Luminaire class: Class II SELV
IP Class: IP20

Energy and approvals

Contains light source of energy class: B
Breeam: Fulfil Hea 01 for flicker free lighting

Materials and finish

Housing: Sheet steel
Colour: White
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Recessed, Indoor
Module: 120x1200
Connection: 5 pol Linect / screwless terminal block

Dimensions

Length (mm) L: 1195
Width (mm) W: 118
Height (mm) H: 35
Ceiling void depth (mm): 35
Weight (kg) gross/net: 1.5 / 1.3

Packaging

Packing dimensions (mm): 1350 x 135 x 54



7 0 2 1 9 8 2 1 2 6 9 5 6