

Rax Soft 200 Connect Wireless



Rax Soft 200 Satin 3070lm Ra>80 Connect Wireless

Article code: 212773+820506
EAN: 7021982127731+7021988205068



Electrical

Wattage: 26W
System wattage: 26W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 22, B16: 35, C10: 36, C16: 60

Light technic

Type of light source: LED
Luminous flux: 3070lm
Efficacy: 118 lm/W
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Direct
Optic: Satin Matt Reflector
Beam angle: 62°

Control/Dimming

Type: Connect Wireless
Driver: 700mA

Protection

Luminaire class: Class II SELV
IK Class: IK08
IP Class: IP44/IP20

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Flame retardant polycarbonate
Colour: White/Satin mat
Optics: Polycarbonat (PC)

Mounting/Connection

Mounting: Recessed, Indoor
Connection: 3 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 93
Diameter (mm) D: 216
Cut-out (mm): 200
Weight (kg) gross/net: 1.2 / 1

Packaging

Packing dimensions (mm): 240 x 240 x 102



7021982127731+7021988205068