

EcoLine Connect



Ecoline Connect 1600 White 4403lm 4000K Ra>90 Connect

Article code: 212819
EAN: 7021982128196



Electrical

System wattage: 36W
Voltage: 220-240V
Frequency (Hz): 50/60Hz

Light technic

Type of light source: LED
Light source included: Yes
Luminous flux: 4403lm
Efficacy: 122 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>90
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Light distribution: Direct
Optic: Opalprism

Control/Dimming

Type: Connect

Protection

Luminaire class: Class I
IP Class: IP20

Energy and approvals

Contains light source of energy class: C

Materials and finish

Housing: Sheet steel
Optics: Acrylic (PMMA)

Mounting/Connection


Mounting: Suspended or surface, Indoor
Module: 1600
Connection: 3 pole Screwless terminal block

Dimensions

Length (mm) L: 1600
Width (mm) W: 166
Height (mm) H: 55
Weight (kg) gross/net: 5.5 / 5

Packaging

Packing dimensions (mm): 1620 x 180 x 70



H (m)	Minor movements		Major movements	
	X1 (m)	Y1 (m)	X2 (m)	Y2 (m)
2.4	1.9	2.9	2.9	4.3
3	2.4	3.6	3.6	5.4



7 0 2 1 9 8 2 1 2 8 1 9 6