

# Zip Inspire



## Zip Inspire 300 White 950lm 3000K Ra 98 Trailing edge

Article code: 320773  
EAN: 7021983207739



### Electrical

System wattage: 15W  
Voltage: 220-240V  
Frequency (Hz): 50/60Hz  
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

### Light technic

Type of light source: LED  
Luminous flux: 950lm  
Efficacy: 63 lm/W  
Colour temperature: 3000K  
Colour rendering (Ra): Ra 98  
MacAdams factor: SDCM: 2  
Lifetime: L90/B10>100,000  
Light distribution: Direct  
Beam angle: 55°  
Visible flicker (PstLM): 0.1  
Stroboscopic flicker (SVM): 0.1

### Control/Dimming

Type: Trailing edge

### Protection

Luminaire class: Class II SELV  
IP Class: IP20

### Energy and approvals

Contains light source of energy class: E  
Breeam: Fulfils Hea 01 for flicker free lighting

### Materials and finish

Housing: Aluminium  
Colour: White (RAL 9003)

### Mounting/Connection

Mounting: Indoor  
Module: 300  
Connection: Zip track (adapter included)

### Dimensions

Length (mm) L: 300  
Width (mm) W: 59  
Height (mm) H: 85  
Weight (kg) gross/net: 1.144 / 1.05

### Packaging

Packing dimensions (mm): 92 x 66 x 308

