

Tube Micro S



Tube Micro S White 370lm 3000K Ra 98 Trailing edge

Article code: 320807
EAN: 7021983208071



Electrical

System wattage: 7W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 180, B16: 290, C10: 180, C16: 290

Light technic

Type of light source: LED
Luminous flux: 370lm
Efficacy: 53 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra 98
MacAdams factor: SDCM: 2
Lifetime: L90/B10>50,000
Light distribution: Direct
Optic: Reflector
Beam angle: 36°
UGR: UGR<19
Visible flicker (PstLM): 0
Stroboscopic flicker (SVM): 0.01

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IP Class: IP20

Energy and approvals

Contains light source of energy class: F
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)
Optics: UV-stabilized polycarbonate

Mounting/Connection



Mounting: Surface, Indoor

Dimensions

Length (mm) L: 135
Width (mm) W: 39
Height (mm) H: 25
Diameter (mm) D: 102
Weight (kg) gross/net: 0.523 / 0.428

Packaging

Packing dimensions (mm): 185 x 106 x 106



7 0 2 1 9 8 3 2 0 8 0 7 1