

# Tube Micro S



## Tube Micro S Black 360lm 2700K Ra 98 Trailing edge

Article code: 320809  
EAN: 7021983208095



### Electrical

System wattage: 7W  
Voltage: 220-240V  
Frequency (Hz): 50/60Hz  
Max. luminaires per circuit breaker: B10: 180, B16: 290, C10: 180, C16: 290

### Light technic

Type of light source: LED  
Luminous flux: 360lm  
Efficacy: 51 lm/W  
Colour temperature: 2700K  
Colour rendering (Ra): Ra 98  
MacAdams factor: SDCM: 2  
Lifetime: L90/B10>50,000  
Light distribution: Direct  
Optic: Reflector  
Beam angle: 36°  
UGR: UGR<19  
Visible flicker (PstLM): 0  
Stroboscopic flicker (SVM): 0.01

### Control/Dimming

Type: Trailing edge

### Protection

Luminaire class: Class II  
IP Class: IP20

### Energy and approvals

Contains light source of energy class: F  
Breeam: Fulfils Hea 01 for flicker free lighting

### Materials and finish

Housing: Aluminium  
Colour: Black (RAL 9004)  
Optics: UV-stabilized polycarbonate

### Mounting/Connection



Mounting: Surface, Indoor

### Dimensions

Length (mm) L: 135  
Width (mm) W: 39  
Height (mm) H: 25  
Diameter (mm) D: 102  
Weight (kg) gross/net: 0.523 / 0.428

### Packaging

Packing dimensions (mm): 185 x 106 x 106



7 0 2 1 9 8 3 2 0 8 0 9 5