

Inspire R



Inspire R White 600 3160lm 4000K Ra>80 DALI-2

Article code: 320907
EAN: 7021983209078



Electrical

System wattage: 23W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED
Luminous flux: 3160lm
Efficacy: 137 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B10>100,000
Lifetime: L80/B10>70,000
Light distribution: Direct
Optic: Cubic Optic Black
Beam angle: 60°
UGR: UGR<19
Visible flicker (PstLM): 0.01
Stroboscopic flicker (SVM): 0
Photobiological safety: RG 1

Control/Dimming

Type: DALI-2

Protection

Luminaire class: Class II SELV
IP Class: IP20

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Optics: Polycarbonat (PC)

Mounting/Connection



Mounting: Recessed, Indoor
Module: Recessed
Connection: Screwless terminal block

Dimensions

Length (mm) L: 595
Width (mm) W: 62
Height (mm) H: 40
Weight (kg) gross/net: 1.039 / 0.884

Packaging

Packing dimensions (mm): 885 x 85 x 43



7 0 2 1 9 8 3 2 0 9 0 7 8