

# Frame Round Maxi



## Frame Round Maxi Black 1990lm 3000K Ra>80 Trailing edge

Article code: 605151  
EAN: 7021986051513



### Electrical

System wattage: 19W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 31, B16: 50, C10: 52, C16: 85

### Light technic

Type of light source: LED  
Luminous flux: 1990lm  
Efficacy: 105 lm/W  
Colour temperature: 3000K  
Colour rendering (Ra): Ra>80  
MacAdams factor: SDCM: 3  
Lifetime: L70/B20>100,000  
Lifetime: L80/B20>75,000  
Light distribution: Direct  
Optic: Opal  
Beam angle: 110°  
Photobiological safety: RG 0

### Control/Dimming

Type: Trailing edge

### Protection

Luminaire class: Class II  
IK Class: IK10  
IP Class: IP66  
Fire protection class: 850°C - 30s

### Energy and approvals

Contains light source of energy class: C  
Breeam: Fulfils Hea 01 for flicker free lighting  
BVB: Yes  
ULOR (Yes, when ceiling mounted)  
Sunda Hus: C-

### Materials and finish

Housing: Aluminium  
Colour: Black (RAL 9004)  
Optics: UV-stabilized polycarbonate

### Mounting/Connection

Mounting: Surface, Indoor / Outdoor  
Connection: Screwless terminal block

### Dimensions

Height (mm) H: 77  
Diameter (mm) D: 325  
Weight (kg) gross/net: 3.1 / 2.7

### Packaging

Packing dimensions (mm): 332 x 332 x 92



7 0 2 1 9 8 6 0 5 1 5 1 3