

# Frame



## Frame Graphite 670lm 3000K Ra>80 Twilight

Article code: 605562  
EAN: 7021986055627



### Electrical

System wattage: 8W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 77, B16: 123, C10: 77, C16: 123

### Light technic

Type of light source: LED  
Luminous flux: 670lm  
Efficacy: 84 lm/W  
Colour temperature: 3000K  
Colour rendering (Ra): Ra>80  
MacAdams factor: SDCM: 3  
Lifetime: L70/B20>100,000  
Lifetime: L80/B20>75,000  
Light distribution: Direct  
Optic: Opal  
Beam angle: 110°  
Photobiological safety: RG 0

### Control/Dimming

Type: Twilight

### Protection

Luminaire class: Class II  
IK Class: IK10  
IP Class: IP66  
Fire protection class: 850°C - 30s

### Energy and approvals

Contains light source of energy class: C  
Breeam: Fulfils Hea 01 for flicker free lighting  
BVB: Yes  
ULOR ( : Yes, when ceiling mounted

### Materials and finish

Housing: Aluminium  
Colour: Graphite  
Optics: UV-stabilized polycarbonate

### Mounting/Connection



Mounting: Surface, Indoor / Outdoor  
Connection: Screwless terminal block

### Dimensions

Length (mm) L: 320  
Width (mm) W: 180  
Height (mm) H: 77  
Weight (kg) gross/net: 2.47 / 1.9

### Packaging

Packing dimensions (mm): 328 x 188 x 92



7 0 2 1 9 8 6 0 5 5 6 2 7