

Disc 285x285



Disc 285X285 White 2280lm 3000K Ra>80 Emergency 3H

Article code: 606064
EAN: 7021986060645



• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 20W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 40, B16: 65, C10: 55, C16: 100

Light technic

Type of light source: LED
Luminous flux: 2280lm
Emergency lumen: EM 380lm
Efficacy: 114 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>100,000
Lifetime: L90>50,000
Minimum ambient temperature: 0°C
Light distribution: Direct
Optic: Opalprism
Beam angle: 85°
UGR: UGR<25

Control/Dimming

Type: Emergency 3H

Protection

Luminaire class: Class II
IK Class: IK10
IP Class: IP20

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: White
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Surface, Indoor
Connection: Screwless terminal block

Dimensions

Length (mm) L: 283
Width (mm) W: 283
Height (mm) H: 55
Weight (kg) gross/net: 2.285 / 2.098

Packaging

Packing dimensions (mm): 303 x 308 x 60



7 0 2 1 9 8 6 0 6 0 6 4 5