

Curve White 580lm 2700K Ra>80 Trailing edge

Article code: 611340
EAN: 7021986113402



Electrical

System wattage: 7W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light technic

Type of light source: LED
Luminous flux: 580lm
Efficacy: 83 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L90/B10>50,000
Lifetime: L80/B10>100,000
Light distribution: Direct
Optic: Glass Clear
Beam angle: 110°/110°
Photobiological safety: RG 0

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class I
IK Class: IK06
IP Class: IP65

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfil Hea 01 for flicker free lighting
BVB: Yes
Sunda Hus: C-

Materials and finish

Housing: Aluminium
Colour: Matte white (RAL 9003)
Optics: Tempered glass

Mounting/Connection


Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Width (mm) W: 320
Height (mm) H: 60
Depth (D): 103
Weight (kg) gross/net: 1.68 / 1.4

Packaging

Packing dimensions (mm): 330 x 120 x 70



7 0 2 1 9 8 6 1 1 3 4 0 2