

Edge Direct Graphite 570lm 3000K Ra>80 Trailing edge

Article code: 611358
EAN: 7021986113587
Replaces: 623361



Electrical
System wattage: 7W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 15, B16: 25, C10: 31, C16: 50

Light technic
Type of light source: LED
Luminous flux: 570lm
Efficacy: 81 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L90/B10>50,000
Lifetime: L80/B10>100,000
Light distribution: Direct
Optic: Glass Frosted

Control/Dimming
Type: Trailing edge

Protection
Luminaire class: Class I
IK Class: IK06
IP Class: IP65

Energy and approvals
Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting
ULOR (Yes

Materials and finish
Housing: Aluminium
Colour: Graphite
Optics: Tempered glass

Mounting/Connection
Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions
Width (mm) W: 320
Height (mm) H: 60
Depth (D): 103
Weight (kg) gross/net: 1.84 / 1.7

Packaging
Packing dimensions (mm): 330 x 120 x 70

