

Trio White 400lm 2700K Ra>80 Trailing edge

Article code: 611524
 EAN: 7021986115246



Electrical

System wattage: 7W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light technic

Type of light source: LED
 Luminous flux: 400lm
 Efficacy: 57 lm/W
 Colour temperature: 2700K
 Colour rendering (Ra): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L70/B10>50,000
 Light distribution: Direct
 Optic: Opal
 Beam angle: 130°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class I
 IK Class: IK10
 IP Class: IP65
 Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: C
 Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
 Colour: White (RAL 9003)
 Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Indoor / Outdoor
 Connection: Screwless terminal block

Dimensions

Length (mm) L: 320
 Width (mm) W: 180
 Height (mm) H: 320
 Depth (D): 102
 Weight (kg) gross/net: 1.8 / 1.5

Packaging

Packing dimensions (mm): 330 x 190 x 110

