

Metro White 360lm 2700K Ra>80 Trailing edge

Article code: 611693
EAN: 7021986116939



Electrical

Wattage: 2x4,5W
System wattage: 9W
Voltage: 220-240V

Light technic

Type of light source: LED
Socket: GU10
Light source included: Yes
Luminous flux: 360lm
Efficacy: 40 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 4
Lifetime: L70/B50>40,000
Light distribution: Direct
Optic: Glass Clear
Beam angle: 35°/35°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IK Class: IK07
IP Class: IP65

Energy and approvals

Contains light source of energy class: G
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes
Sunda Hus: C+

Materials and finish

Housing: Aluminium
Colour: White (RAL 9003)
Optics: Tempered glass

Mounting/Connection

Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Length (mm) L: 160
Width (mm) W: 90
Height (mm) H: 215
Depth (D): 147
Weight (kg) gross/net: 1.476 / 1.223

Packaging

Packing dimensions (mm): 230 x 155 x 100

