

Metro Black 180lm 2700K Ra>80 Trailing edge

Article code: 614691
EAN: 7021986146912



Electrical

System wattage: 4.5W
Voltage: 220-240V

Light technic

Type of light source: LED
Socket: GU10
Light source included: Yes
Luminous flux: 180lm
Efficacy: 40 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 4
Lifetime: L70/B50>40,000
Light distribution: Direct
Optic: Glass Clear
Beam angle: 35°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IK Class: IK07
IP Class: IP65

Energy and approvals

Contains light source of energy class: G
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes
ULOR (: Yes
Sunda Hus: C+

Materials and finish

Housing: Aluminium
Colour: Black (RAL 9004)
Optics: Tempered glass

Mounting/Connection



Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Width (mm) W: 90
Height (mm) H: 120
Depth (D): 147
Weight (kg) gross/net: 1.08 / 0.9

Packaging

Packing dimensions (mm): 160 x 100 x 135



7 0 2 1 9 8 6 1 4 6 9 1 2