

Spike Black w/ outlet 880lm 3000K Ra>80 Trailing edge

Article code: 614912
EAN: 7021986149128

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 10W
Voltage: 220-240V

Light technic

Type of light source: LED
Luminous flux: 880lm
Efficacy: 88 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B50>50,000
Light distribution: Direct
Optic: Opal
Beam angle: 95°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class I
IK Class: IK08
IP Class: IP44

Energy and approvals

Contains light source of energy class: C
Breem: Fulfil Hea 01 for flicker free lighting
ULOR (Yes

Materials and finish

Housing: Aluminium
Colour: Black (RAL 9004)
Optics: UV-stabilized polycarbonate

Mounting/Connection



Mounting: Surface, Outdoor
Connection: Screwless terminal block

Dimensions

Width (mm) W: 171
Height (mm) H: 173
Depth (D): 155
Weight (kg) gross/net: 1.61

Packaging

Packing dimensions (mm): 180 x 165 x 185



7 0 2 1 9 8 6 1 4 9 1 2 8