

Fevik Asymmetric



Fevik Asymmetric Graphite Asymmetric 2470lm 4000K Ra>70 On/Off

Article code: 623251
EAN: 7021986232516



Electrical

System wattage: 25W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 9, B16: 16, C10: 15, C16: 26

Light technic

Type of light source: LED
Luminous flux: 2470lm
Efficacy: 99 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>70
MacAdams factor: SDCM: 3
Lifetime: L90/B10>100,000
Light distribution: Asymmetric
Optic: Glass Clear

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I
IK Class: IK10
IP Class: IP65
Surge protection: Integrated (min. 4 kV)

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes
ULOR (: Yes

Materials and finish

Housing: Die-cast aluminium
Colour: Graphite
Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Surface, Outdoor
Connection: Screwless terminal block
Wind projected area: 0,0233m² - Max 4 kg

Dimensions

Length (mm) L: 300
Width (mm) W: 223
Height (mm) H: 110
Depth (D): 276
Weight (kg) gross/net: 3.96 / 3.3

Packaging

Packing dimensions (mm): 276 x 223 x 110

