

Metro Graphite Ceiling 180lm 2700K Ra>80 Trailing edge

Article code: 623696
EAN: 7021986236965



Electrical

System wattage: 4.5W
Voltage: 220-240V

Light technic

Type of light source: LED
Socket: GU10
Light source included: Yes
Luminous flux: 180lm
Efficacy: 40 lm/W
Colour temperature: 2700K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 4
Lifetime: L70/B50>40,000
Light distribution: Direct
Optic: Glass Clear
Beam angle: 35°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class I
IK Class: IK07
IP Class: IP65

Energy and approvals

Contains light source of energy class: G
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes
ULOR (: Yes
Sunda Hus: C+

Materials and finish

Housing: Aluminium
Colour: Graphite
Optics: Tempered glass

Mounting/Connection

Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Height (mm) H: 120
Diameter (mm) D: 90
Weight (kg) gross/net: 0.828 / 0.69

Packaging

Packing dimensions (mm): 100 x 100 x 150

