

Opus R Graphite 580lm 3000K Ra>80 Trailing edge

Article code: 623742  
EAN: 7021986237429



Electrical

Wattage: 10W  
System wattage: 10W  
Voltage: 220-240V

Light technic

Type of light source: LED  
Luminous flux: 580lm  
Efficacy: 58 lm/W  
Colour temperature: 3000K  
Colour rendering (Ra): Ra>80  
MacAdams factor: SDCM: 3  
Lifetime: L70/B50>50,000  
Light distribution: Direct  
Optic: Opal  
Beam angle: 360°  
Photobiological safety: RG 0

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II  
IK Class: IK10  
IP Class: IP65

Energy and approvals

Contains light source of energy class: C  
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium  
Colour: Graphite  
Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Onto surfaces or ground anchor, Outdoor  
Connection: Screwless terminal block

Dimensions

Height (mm) H: 396  
Diameter (mm) D: 216  
Weight (kg) gross/net: 4.236 / 3.95

Packaging

Packing dimensions (mm): 230 x 230 x 410

