

Kjevik Black 2060lm 3000K Ra>80 DALI-2

Article code: 623801  
EAN: 7021986238013

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 26W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 31, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED  
Luminous flux: 2060lm  
Efficacy: 79 lm/W  
Colour temperature: 3000K  
Colour rendering (Ra): Ra>80  
MacAdams factor: SDCM: 2  
Lifetime: L90/B10>100,000  
Light distribution: Direct  
Photobiological safety: RG 1

Control/Dimming

Type: DALI-2

Protection

Luminaire class: Class II  
IK Class: IK10  
IP Class: IP66

Energy and approvals

Contains light source of energy class: D  
Breeam: Fulfils Hea 01 for flicker free lighting  
ULOR ( Yes

Materials and finish

Housing: Aluminium  
Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Outdoor

Dimensions

Height (mm) H: 1010  
Diameter (mm) D: 200  
Weight (kg) gross/net: 10.75 / 8.7

Packaging

Packing dimensions (mm): 1030 x 215 x 215  
Number per pack: 1

