

Herning Bollard & Pole



Herning Mini Ø60 Black Polehead 580/620/1220/1300lm 3000/4000K Ra>80

Trailing edge

Article code: 623978
EAN: 7021986239782



Electrical

Wattage: 8W/17W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 30, B16: 47, C10: 50, C16: 80

Light technic

Type of light source: LED
Luminous flux: 580/620/1220/1300lm
Efficacy: 73/78/72/76lm/W
Colour temperature: 3000/4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B20>50,000
Light distribution: Direct
Optic: Glass
UGR: UGR<22/25
Photobiological safety: RG 1

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IK Class: IK06
IP Class: IP65

Energy and approvals

Contains light source of energy class: E
ULOR (Yes

Materials and finish

Housing: Aluminium

Mounting/Connection

Mounting: Pole, wall, bollard or earthing rod, Outdoor
Module: Ø60
Cable: Cable 2x1mm² 3m

Dimensions

Length (mm) L: 342
Width (mm) W: 182
Height (mm) H: 144
Weight (kg) gross/net: 2.55 / 2.02

Packaging

Packing dimensions (mm): 342 x 190 x 200

