

## SG Hovden Graphite Midi 1140lm 3000K Ra>80 Trailing edge

Article code: 630005  
EAN: 7021986300055



### Electrical

System wattage: 12W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 47, B16: 67, C10: 47, C16: 67

### Light technic

Type of light source: LED  
Luminous flux: 1140lm  
Efficacy: 95 lm/W  
Colour temperature: 3000K  
Colour rendering (Ra): Ra>80  
MacAdams factor: SDCM: 3  
Lifetime: L70/B10>100,000  
Light distribution: Direct  
Optic: Lens  
Beam angle: 36°  
Visible flicker (PstLM): 0  
Stroboscopic flicker (SVM): 0.01

### Control/Dimming

Type: Trailing edge

### Protection

Luminaire class: Class I  
IK Class: IK10  
IP Class: IP67

### Energy and approvals

Contains light source of energy class: F  
Breeam: Fulfils Hea 01 for flicker free lighting  
BVB: Yes  
ULOR ( : Yes, up to 35° tilt angle

### Materials and finish

Housing: Aluminium  
Colour: Graphite  
Optics: Acrylic (PMMA)

### Mounting/Connection

Mounting: Surface, Outdoor  
Cable: Cable 2m  
Connection: Includes cable and plug

### Dimensions

Length (mm) L: 100  
Width (mm) W: 61  
Height (mm) H: 116  
Weight (kg) gross/net: 0.969 / 0.881

### Packaging

Packing dimensions (mm): 160 x 120 x 80

