

SG Hovden Graphite Mini 570lm 2700K Ra>80 Trailing edge

Article code: 630063
 EAN: 7021986300635
 Replaces: 614001



Electrical

System wattage: 8W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 69, B16: 98, C10: 69, C16: 98

Light technic

Type of light source: LED
 Luminous flux: 570lm
 Efficacy: 71 lm/W
 Colour temperature: 2700K
 Colour rendering (Ra): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L70/B10>100,000
 Light distribution: Direct
 Optic: Lens
 Beam angle: 36°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class I
 IK Class: IK10
 IP Class: IP67

Energy and approvals

Contains light source of energy class: F
 Breeam: Fulfils Hea 01 for flicker free lighting
 BVB: Yes
 ULOR (: Yes, up to 47° tilt angle

Materials and finish

Housing: Aluminium
 Colour: Graphite
 Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Surface, Outdoor
 Cable: Cable 2m
 Connection: Includes cable and plug

Dimensions

Length (mm) L: 90
 Width (mm) W: 46
 Height (mm) H: 100
 Weight (kg) gross/net: 0.66 / 0.6

Packaging

Packing dimensions (mm): 150 x 125 x 65

