

Piano 2000 Graphite 1650lm 3000K Ra>80 Trailing edge

Article code: 633876
EAN: 7021986338768



Electrical

System wattage: 14W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 44, B16: 30, C10: 44, C16: 51

Light technic

Type of light source: LED
Luminous flux: 1650lm
Efficacy: 118 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B50>100,000
Light distribution: Direct/Indirect
Optic: Opal
Beam angle: 110°
Photobiological safety: RG 0

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class I
IK Class: IK10
IP Class: IP65
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfil Hea 01 for flicker free lighting
BVB: Yes
Sunda Hus: C+

Materials and finish

Housing: Aluminium
Colour: Graphite
Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Outdoor
Module: 2000
Connection: Screwless terminal block

Dimensions

Height (mm) H: 105
Diameter (mm) D: 340
Weight (kg) gross/net: 2.6 / 2.1

Packaging

Packing dimensions (mm): 352 x 352 x 115

