

Artes Midi Graphite 1010lm 3000K Ra>80 Trailing edge

Article code: 641713
EAN: 7021986417135



Electrical

System wattage: 32W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 1010lm
Efficacy: 32 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B10>100,000
Lifetime: L80/B50>80,000
Optic: Lens
Beam angle: 60°
Visible flicker (PstLM): 0.07
Stroboscopic flicker (SVM): 0.07
Photobiological safety: RG 1

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class II
IK Class: IK10
IP Class: IP65

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes
ULOR (: Yes, for direct only

Materials and finish

Housing: Aluminium
Colour: Graphite
Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Wall, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Length (mm) L: 205
Width (mm) W: 205
Height (mm) H: 125
Weight (kg) gross/net: 2.63 / 2.385

Packaging

Packing dimensions (mm): 220 x 212 x 137

