

Langfoss Graphite 20430lm 3000K Ra>70 On/Off

Article code: 641935
EAN: 7021986419351



Electrical

System wattage: 158W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 2, B16: 4, C10: 4, C16: 6

Light technic

Type of light source: LED
Light source included: Yes
Luminous flux: 20430lm
Efficacy: 129 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>70
MacAdams factor: SDCM: 3
Lifetime: L90/B10>50,000
Lifetime: L80/B20>75,000
Light distribution: Asymmetric
Optic: Lens

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I
IK Class: IK08
IP Class: IP66
Surge protection: Integrated (min. 4 kV)

Energy and approvals

ULOR (Yes, up to 21° tilt angle

Materials and finish

Housing: Die-cast aluminium
Colour: Graphite
Optics: Tempered glass

Mounting/Connection

Mounting: Indoor / Outdoor
Cable: Cable 3x1mm² 2m, H07RN-F
Wind projected area: 0,1245m² - Max 16,2 kg

Dimensions

Length (mm) L: 478
Width (mm) W: 314
Height (mm) H: 85
Weight (kg) gross/net: 9.9 / 8.7

Packaging

Packing dimensions (mm): 508 x 325 x 93

