

Sidewalk



Sidewalk 2000 Graphite 1500lm 4000K Ra>80 Trailing edge

Article code: 643832
EAN: 7021986438321



Electrical

System wattage: 14W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 1500lm
Efficacy: 107 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B50>100,000
Light distribution: Direct
Optic: Opal
Beam angle: 110°

Control/Dimming

Type: Trailing edge

Protection

Luminaire class: Class I
IK Class: IK10
IP Class: IP65
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: Graphite
Optics: UV-stabilized polycarbonate

Mounting/Connection



Mounting: Surface, Indoor / Outdoor
Module: 2000
Connection: Screwless terminal block

Dimensions

Length (mm) L: 300
Width (mm) W: 300
Height (mm) H: 87
Weight (kg) gross/net: 3 / 2.28

Packaging

Packing dimensions (mm): 310 x 310 x 100



7 0 2 1 9 8 6 4 3 8 3 2 1