

CircLED Single



CircLED Single Top Adjustable 5-17° 1640lm 4000K Ra>80 On/Off

Article code: 8246082774
EAN: 5703821165679

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 14W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED
Luminous flux: 1640lm
Efficacy: 117 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Single Lens
Optic: Lens

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I
IK Class: IK09
IP Class: IP66
Surge protection: Integrated (min. 4 kV)

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Die-cast aluminium
Colour: Grey (structure 2150 sablé)
Optics: Tempered glass

Mounting/Connection



Mounting: Post - adjustable head 5-17°, Outdoor
Cable: Cable 3x1mm² 6,0m
Wind projected area: 0,0415m² - Max 6,2 kg

Dimensions

Length (mm) L: 460
Width (mm) W: 390
Height (mm) H: 185
Weight (kg) gross/net: 8.2 / 8

Packaging

Packing dimensions (mm): 525 x 395 x 210



5 7 0 3 8 2 1 1 6 5 6 7 9