

CircLED Single



CircLED Single Grey Side 3320lm 4000K Ra>80 On/Off

Article code: 8246086178
EAN: 5703821166379

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 30W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light technic

Type of light source: LED
Luminous flux: 3320lm
Efficacy: 111 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 2
Lifetime: L90/B10>100,000
Light distribution: Single Lens
Optic: Lens

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class II
IK Class: IK09
IP Class: IP66
Surge protection: Integrated (min. 4 kV)

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting
ULOR (Yes / Yes, up to 17° tilt angle

Materials and finish

Housing: Die-cast aluminium
Colour: Grey (structure 2150 sablé)
Optics: Tempered glass

Mounting/Connection



Mounting: Pole - Side (Ø48mm), Outdoor
Cable: Cable 2x1mm² 10m
Wind projected area: 0,0415m² - Max 6,2 kg

Dimensions

Length (mm) L: 523
Width (mm) W: 390
Height (mm) H: 135
Weight (kg) gross/net: 8.2 / 8

Packaging

Packing dimensions (mm): 525 x 395 x 210



5 7 0 3 8 2 1 1 6 6 3 7 9