

# CircLED Single



## CircLED Single Grey Top Adjustable 5-17° 2430lm 4000K Ra>80 On/Off

Article code: 8246086369  
EAN: 5703821166348

• = This article is produced by order, with an expected delivery time of 3-4 weeks.



### Electrical

System wattage: 21W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

### Light technic

Type of light source: LED  
Luminous flux: 2430lm  
Efficacy: 116 lm/W  
Colour temperature: 4000K  
Colour rendering (Ra): Ra>80  
MacAdams factor: SDCM: 2  
Lifetime: L90/B10>100,000  
Light distribution: Single Lens  
Optic: Lens

### Control/Dimming

Type: On/Off

### Protection

Luminaire class: Class II  
IK Class: IK09  
IP Class: IP66  
Surge protection: Integrated (min. 4 kV)

### Energy and approvals

Contains light source of energy class: D  
Breeam: Fulfils Hea 01 for flicker free lighting  
ULOR ( Yes / Yes, up to 17° tilt angle

### Materials and finish

Housing: Die-cast aluminium  
Colour: Grey (structure 2150 sablé)  
Optics: Tempered glass

### Mounting/Connection

Mounting: Post - adjustable head 5-17°, Outdoor  
Cable: Cable 2x1mm² 6m  
Wind projected area: 0,0415m² - Max 6,2 kg

### Dimensions

Length (mm) L: 460  
Width (mm) W: 390  
Height (mm) H: 185  
Weight (kg) gross/net: 8.2 / 8

### Packaging

Packing dimensions (mm): 525 x 395 x 210

