

Place Grey 2410lm 3000K Ra>80 DYNADIM

Article code: 8246088215
EAN: 5703821168076



Electrical

System wattage: 21W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 10, B16: 17, C10: 16, C16: 27

Light technic

Type of light source: LED
Luminous flux: 2410lm
Efficacy: 115 lm/W
Colour temperature: 3000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L90/B10>50,000
Lifetime: L80/B10>100,000
Light distribution: Direct

Control/Dimming

Type: DYNADIM

Protection

Luminaire class: Class II
IK Class: IK10
IP Class: IP66
Surge protection: Integrated (min. 4 kV)

Energy and approvals

Contains light source of energy class: C
BVB: Yes
Sunda Hus: C+

Materials and finish

Housing: Die-cast aluminium
Colour: Grey (structure 2150 sablé)
Optics: Polycarbonat (PC)

Mounting/Connection

Mounting: Post - top (Ø60mm), Outdoor
Cable: Cable 2x1mm² 6m
Wind projected area: 0,0775m² - Max 10 kg

Dimensions

Height (mm) H: 291
Diameter (mm) D: 600
Weight (kg) gross/net: 7.6 / 7.44

Packaging

Packing dimensions (mm): 625 x 625 x 300

