

EcoLine Office 1500 White 4710lm 4000K Ra>80 On/Off

Article code: 8246090559
EAN: 5703821172486



Electrical

System wattage: 35W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 16, B16: 26, C10: 27, C16: 44
Leakage current (mA): 0.54

Light technic

Type of light source: LED
Luminous flux: 4710lm
Efficacy: 135 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B10>50,000
Light distribution: Direct
Optic: Double parabolic louvre, satin matt
UGR: UGR<19

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I
IP Class: IP20

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Sheet steel
Colour: White (Pure white, 25% gloss)
Optics: Aluminium

Mounting/Connection



Mounting: Suspended or surface, Indoor
Module: 1500
Connection: Screwless terminal block

Dimensions

Length (mm) L: 1500
Width (mm) W: 142
Height (mm) H: 63
Weight (kg) gross/net: 7.7 / 7.5

Packaging

Packing dimensions (mm): 1515 x 146 x 68



5 7 0 3 8 2 1 1 7 2 4 8 6