

EcoLine Office



EcoLine Office 1500 White 5140lm 4000K Ra>80 On/Off

Article code: 8246090591
EAN: 5703821172509



Electrical

System wattage: 34W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 16, B16: 26, C10: 27, C16: 44
Leakage current (mA): 0.54

Light technic

Type of light source: LED
Luminous flux: 5140lm
Efficacy: 151 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B10>50,000
Light distribution: Direct/Indirect 65/35%
Optic: Double parabolic louvre, satin matt
UGR: UGR<16

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class I
IP Class: IP20

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Sheet steel
Colour: White (Pure white, 25% gloss)
Optics: Aluminium

Mounting/Connection



Mounting: Suspended, Indoor
Module: 1500
Wire set: 2x2m wire kit w/loop M13 w/2 brackets
Cable: Cable 3x0,75mm² 2,5m w/ Schuko white
Connection: Screwless terminal block

Dimensions

Length (mm) L: 1500
Width (mm) W: 142
Height (mm) H: 81
Weight (kg) gross/net: 8.2 / 8

Packaging

Packing dimensions (mm): 1555 x 146 x 95



5 7 0 3 8 2 1 1 7 2 5 0 9