

Lineal Surface



Lineal Corner Black 1830lm 4000K Ra>80 DALI-2 / Push Dim

Article code: 8246094733
EAN: 5703821178112



Electrical

System wattage: 17W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 15, B16: 24, C10: 25, C16: 41
Leakage current (mA): 0.29

Light technic

Type of light source: LED
Luminous flux: 1830lm
Efficacy: 108 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L80/B10>100,000
Lifetime: L93/>50,000
Light distribution: Direct
UGR: UGR<28
Photobiological safety: RG 0

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class I
IK Class: IK08
IP Class: IP20

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfil Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: Black

Mounting/Connection


Mounting: Suspended, Indoor
Module: Corner
Wire set: 1x2m wire kit w/ceiling bracket
Connection: 5-pole Winsta mini with 5x2,5mm2 through wiring

Dimensions


Length (mm) L: 642
Width (mm) W: 42
Height (mm) H: 70
Depth (D): 571
Weight (kg) gross/net: 2.8 / 2.6

Packaging

Packing dimensions (mm): 640 x 585 x 75



Module	W	H	L1	L2	L3
590x640mm	42	70	592	642	571
End cap	42	70	3	28	



5 7 0 3 8 2 1 1 7 8 1 1 2