Lineal Suspended



Lineal suspended 1400 White 4960lm 4000K Ra>80 DALI Emergency 3H

Article code: 8246094856 EAN: 5703821178532

= This article is produced by order, with an expected delivery time of 3-4 weeks.

CE IP20 EL

Electrical System wattage: 37W Voltage: 220-240V

Light technic

Type of light source: LED Luminous flux: 4960lm Emergency lumen: EM 410 lm 134 lm/W Efficacy: Colour temperature: 4000K Colour rendering (Ra): Ra>80 MacAdams factor: SDCM: 3 Lifetime: L80/B10>100,000 L93/>50,000 Lifetime: 0°C Minimum ambient temperature: Direct/Indirect 50/50% Light distribution: UGR: UGR<22 Photobiological safety: RG 1

Control/Dimming

DALI Emergency 3H Type:

Protection

Luminaire class: Class I IP Class: IP20

Energy and approvals

Contains light source of energy class:

Materials and finish

Housing: Aluminium Colour: White

Mounting/Connection

Mounting: Suspended, Indoor Module: Wire set: 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring Connection:


Dimensions

1401 Length (mm) L: Width (mm) W: 42 Height (mm) H: 70 Weight (kg) gross/net: 3.3 / 3.1

Packaging

Packing dimensions (mm): 1490 x 44 x 71





D

