

DiLED IV



DiLED Iv 599x599 White 4040lm 4000K Ra>80 On/Off

Article code: 8246094953
EAN: 5703821179027



• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 33W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 35, B16: 55, C10: 57, C16: 94

Light technic

Type of light source: LED
Luminous flux: 4040lm
Efficacy: 122 lm/W
Colour temperature: 4000K
Colour rendering (Ra): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L85/B10100,000
Light distribution: Direct
Optic: Prism Optic

Control/Dimming

Type: On/Off

Protection

Luminaire class: Class II
IP Class: IP20

Energy and approvals

Contains light source of energy class: D
Breem: Fulfil Hea 01 for flicker free lighting

Materials and finish

Housing: Sheet steel
Colour: White smooth (Ral 9016 gloss 30)
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Recessed, Indoor
Module: 599x599 C, Clip-in Ceiling
Connection: 5 pol Linect / screwless terminal block

Dimensions

Length (mm) L: 599
Width (mm) W: 599
Height (mm) H: 60
Weight (kg) gross/net: 5 / 4.8

Packaging

Packing dimensions (mm): 605 x 605



5 7 0 3 8 2 1 1 7 9 0 2 7